

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024


Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 1: IDENTIFICATION**

- 1.1 Product identifier:** BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785
- Other means of identification:**  
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses (Industrial user): High performance coatings  
For industrial use only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**  
Belzona Limited  
Claro Road  
HG1 4DS Harrogate - North Yorkshire - England  
Phone: +441423567641  
sds@belzona.com  
https://www.belzona.com
- Belzona Inc.  
14300 NW 60th Ave.  
Miami Lakes  
FL 33014  
UNITED STATES  
Telephone: 1-305-594-4994
- 1.4 Emergency phone number:** VelocityEHS: +1 813-248-0585 (International) (24/7/365)  
US, Puerto Rico & the U.S. Virgin Islands: 1-800-255-3924 (24/7)

**SECTION 2: HAZARD(S) IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**
- NFPA:**  
Health Hazards: 3  
Flammability Hazards: 1  
Instability Hazards: 0  
Special Hazards: Non-applicable
- 29 CFR 1910.1200:**  
Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200  
Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302  
Eye Dam. 1: Serious eye damage, Category 1, H318  
Skin Corr. 1B: Skin corrosion, Category 1B, H314  
Skin Sens. 1B: Sensitisation, skin, Category 1B, H317  
STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372  
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
- 2.2 Label elements:**
- NFPA:**
- 
- 29 CFR 1910.1200:**  
Danger

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024      Revised: 3/26/2025      Version: 1.2 (Replaced 1.1)

**SECTION 2: HAZARD(S) IDENTIFICATION (continued)**



**Hazard statements:**

Acute Tox. 4: H302 - Harmful if swallowed.  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: Kidneys.

**Precautionary statements:**

P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves, protective clothing and eye protection.  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER or doctor.  
P333+P313: If skin irritation or rash occurs: Get medical attention.  
P337+P313: If eye irritation persists: Get medical attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P405: Store locked up.  
P501: Dispose of the contents/container in accordance with all Federal, State/Provincial and local regulations.

**2.3 Hazards not otherwise classified (HNOC):**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:**

**Chemical description:** Formulated polyamines

**Components:**

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: 1761-71-3	4,4'-methylenebis(cyclohexylamine)	30 - <60 %
CAS: 135108-88-2	Copolymer of formaldehyde and aniline, hydrogenated	30 - <60 %
CAS: 61791-55-7	Amines, N-tallow alkyltrimethylenedi-	1 - <5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	M-factor	
	Acute	Chronic
Amines, N-tallow alkyltrimethylenedi- CAS: 61791-55-7	10	1

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

#### SECTION 4: FIRST-AID MEASURES

**4.1 Description of necessary measures:**

Request medical assistance immediately, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Keep the person affected at rest.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

#### SECTION 5: FIRE-FIGHTING MEASURES

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

Carbon dioxide extinguisher (BC), Dry Chemical Powder (ABC) Fire Extinguisher, Foam extinguisher (AB), Water Mist Extinguisher (AC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

For non-emergency personnel:

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights.

Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be assessed in the workplace:



There are no applicable occupational exposure limits for the substances contained in the product

**8.2 Appropriate engineering controls:**


A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
	Filter mask for gases and vapours (Filter type: ABEK)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)
	Continuous flow compressed air line breathing device (Filter type: ABEK)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands



Pictogram	PPE	Remarks
	Chemical protective gloves (Material: Nitrile, Breakthrough time: 10 - 30 min, Thickness: 0.12 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
	Work clothing	Replace before any evidence of deterioration.
	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**



Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**


To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 68 °F:	Liquid
Appearance:	Fluid
Color:	 Grey
Odor:	Ammoniacal
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	>419 °F
Vapour pressure at 68 °F:	<689 Pa
Vapour pressure at 122 °F:	Non-applicable *
Evaporation rate at 68 °F:	Non-applicable *

**Product description:**

Density at 68 °F:	Non-applicable *
Relative density at 68 °F:	0.945 - 1.045
Dynamic viscosity at 68 °F:	1000 mPa·s
Kinematic viscosity at 68 °F:	Non-applicable *
Kinematic viscosity at 104 °F:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 68 °F:	Non-applicable *
Partition coefficient n-octanol/water 68 °F:	Non-applicable *
Solubility in water at 68 °F:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	>482 °F
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	>212 °F
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	950 °F
Lower flammability limit:	Non-applicable *

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Upper flammability limit: Non-applicable \*

**Particle characteristics:**

Median equivalent diameter: Non-applicable \*

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties: Non-applicable \*

Oxidising properties: Non-applicable \*

Corrosive to metals: Non-applicable \*

Heat of combustion: Non-applicable \*

Aerosols-total percentage (by mass) of flammable components: Non-applicable \*

**Other safety characteristics:**

Surface tension at 68 °F: Non-applicable \*

Refraction index: Non-applicable \*

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

**F- Specific target organ toxicity (STOT) - single exposure:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance. Organs affected: Kidneys.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Product-specific toxicological information:**

Acute toxicity		Genus
LD50 oral	373.61 mg/kg	
LD50 dermal	>5000 mg/kg	
LC50 inhalation vapour	>20 mg/L	

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
4,4'-methylenebis(cyclohexylamine) CAS: 1761-71-3	480 mg/kg		Rat
Copolymer of formaldehyde and aniline, hydrogenated CAS: 135108-88-2	300 mg/kg		

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50			
Copolymer of formaldehyde and aniline, hydrogenated CAS: 135108-88-2	LC50	63 mg/L (96 h)	Poecilia reticulata	Fish
	EC50	Non-applicable		
	EC50	43.94 mg/L (72 h)	Desmodesmus subspicatus	Algae
Amines, N-tallow alkyltrimethylenedi- CAS: 61791-55-7	LC50	>0.01 - 0.1 mg/L (96 h)		Fish
	EC50	>0.01 - 0.1 mg/L (48 h)		Crustacean
	EC50	>0.01 - 0.1 mg/L (72 h)		Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	NOEC			
4,4'-methylenebis(cyclohexylamine) CAS: 1761-71-3	NOEC	1 mg/L	N/A	Fish
	NOEC	4 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	100 mg/L
Copolymer of formaldehyde and aniline, hydrogenated CAS: 135108-88-2	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
	BCF	20
Copolymer of formaldehyde and aniline, hydrogenated CAS: 135108-88-2	Pow Log	4.02
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Koc	9988	Henry	Non-applicable
Copolymer of formaldehyde and aniline, hydrogenated CAS: 135108-88-2	Conclusion	Immobile	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

**SECTION 14: TRANSPORT INFORMATION**

**Other information:**

Labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations.

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Copolymer of formaldehyde and aniline, hydrogenated ; Amines, N-tallow alkyltrimethylenedi-)
- 14.3 Transport hazard class(es):** 8  
Labels: 8
- 14.4 Packing group, if applicable:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Physico-Chemical properties: see section 9

Limited quantities: 5 L

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 41-22:



- 14.1 UN number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Copolymer of formaldehyde and aniline, hydrogenated ; Amines, N-tallow alkyltrimethylenedi-)
- 14.3 Transport hazard class(es):** 8  
Labels: 8
- 14.4 Packing group, if applicable:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**
- Special regulations: 274, 223
- EmS Codes: F-A, S-B
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- Segregation group: SGG18
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2025:

**BELZONA® 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 14: TRANSPORT INFORMATION (continued)**



- |  |   |
|--|---|
| <b>14.1 UN number:</b>   | UN2735  |
| <b>14.2 UN proper shipping name:</b>   | AMINES, LIQUID, CORROSIVE, N.O.S. (Copolymer of formaldehyde and aniline, hydrogenated ; Amines, N-tallow alkyltrimethylenedi-) |
| <b>14.3 Transport hazard class(es):</b>  | 8   |
| Labels:  | 8   |
| <b>14.4 Packing group, if applicable:</b>  | III   |
| <b>14.5 Marine pollutant:</b>  | Yes   |
| <b>14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises</b> |   |
| Physico-Chemical properties:   | see section 9   |
| <b>14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):</b>  | Non-applicable  |

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations specific for the product in question:**

- CALIFORNIA LABOR CODE - The Hazardous Substances List: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): *4,4'-methylenebis(cyclohexylamine) (1761-71-3)* ; *Copolymer of formaldehyde and aniline, hydrogenated (135108-88-2)* ; *Amines, N-tallow alkyltrimethylenedi- (61791-55-7)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Non-applicable
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK - Substance List: Non-applicable
- Minnesota - Hazardous substances ERTK: Non-applicable
- New Jersey Worker and Community Right-to-Know Act: Non-applicable
- New York RTK - Substance list: Non-applicable
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: Non-applicable
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: Non-applicable
- Rhode Island - Hazardous substances RTK: Non-applicable
- SB-258 Cleaning Product Right to Know Act : Non-applicable
- The Toxic Substances Control Act (TSCA) : *4,4'-methylenebis(cyclohexylamine) (1761-71-3)* ; *Copolymer of formaldehyde and aniline, hydrogenated (135108-88-2)* ; *Amines, N-tallow alkyltrimethylenedi- (61791-55-7)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Non-applicable

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

**Other legislation:**

Take into consideration other applicable federal, state, and local laws and local regulations.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

**BELZONA<sup>®</sup> 1593 - SOLIDIFIER (LIGHT GREY)  
SN2785**

Date of compilation: 1/19/2024

Revised: 3/26/2025

Version: 1.2 (Replaced 1.1)

**SECTION 16: OTHER INFORMATION (continued)**

Section: 1, 8, 11, 15, 16

**Texts of the legislative phrases mentioned in section 2:**

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: Kidneys.

H317: May cause an allergic skin reaction.

H372: Causes damage to organs through prolonged or repeated exposure.

H302: Harmful if swallowed.

**Advice related to training:**

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 1/19/2024

Revised: 3/26/2025

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET