

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024


Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 1: IDENTIFICATION

- 1.1 Product identifier:** BELZONA® 1813 - BASE
SN2693
- Other means of identification:**
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses (Industrial user): Ceramic coating
For industrial use only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**
Belzona Limited
Claro Road
HG1 4DS Harrogate - North Yorkshire - England
Phone: +441423567641
sds@belzona.com
https://www.belzona.com
- Belzona Inc.
14300 NW 60th Ave.
Miami Lakes
FL 33014
UNITED STATES
Telephone: 1-305-594-4994
- 1.4 Emergency phone number:** VelocityEHS: +1 813-248-0585 (International) (24/7/365)
US, Puerto Rico & the U.S. Virgin Islands: 1-800-255-3924 (24/7)

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
This product contains less than 1% respirable crystalline silica, so it does not require classification
- NFPA:**
Health Hazards: 2
Flammability Hazards: 1
Instability Hazards: 0
Special Hazards: Non-applicable
- 29 CFR 1910.1200:**
Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200
Eye Irrit. 2A: Eye irritation, Category 2A, H319
Repr. 1B: Reproductive toxicity, Category 1B, H360
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
- 2.2 Label elements:**
- NFPA:**
- 
- 29 CFR 1910.1200:**
Danger

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 2: HAZARD(S) IDENTIFICATION (continued)



Hazard statements:

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Repr. 1B: H360 - May damage fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves, protective clothing and eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical attention.

P501: Dispose of the contents/container in accordance with all Federal, State/Provincial and local regulations.

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Epoxy resin

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: 28064-14-4	Bisphenol F diglycidyl ether resin	10 - <30 %
CAS: 30499-70-8	1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane	10 - <30 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

SECTION 4: FIRST-AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Carbon dioxide extinguisher (BC), Dry Chemical Powder (ABC) Fire Extinguisher, Foam extinguisher (AB), Water Mist Extinguisher (AC)

Unsuitable extinguishing media:

Water jet

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024 Revised: 4/11/2025 Version: 1.1 (Replaced 1)

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, manipulation and use.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F
Maximum Temp.: 86 °F
NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Application by plastic applicator or spatula provided. Mix with Solidifier component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:



Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

Pictogram	PPE	Remarks
	Filter mask for gases and vapours (Filter type: ABEK)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)
	Continuous flow compressed air line breathing device (Filter type: ABEK)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**BELZONA® 1813 - BASE
SN2693**


Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)


SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

C.- Specific protection for the hands



Pictogram	PPE	Remarks
	Chemical protective gloves (Material: Nitrile, Breakthrough time: 10 - 30 min, Thickness: 0.12 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
	Work clothing	Replace before any evidence of deterioration.
	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F: Solid
 Appearance: Paste
 Color:  Grey
 Odor: Resin

*Non-applicable due to the nature of the product, not providing information property of its hazards.

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: >374 °F

Vapour pressure at 68 °F: Non-applicable *

Vapour pressure at 122 °F: Non-applicable *

Evaporation rate at 68 °F: Non-applicable *

Product description:

Density at 68 °F: Non-applicable *

Relative density at 68 °F: 2.3 - 2.4

Dynamic viscosity at 68 °F: Non-applicable *

Kinematic viscosity at 68 °F: Non-applicable *

Kinematic viscosity at 104 °F: >20.5 mm²/s

Concentration: Non-applicable *

pH: Non-applicable *

Vapour density at 68 °F: Non-applicable *

Partition coefficient n-octanol/water 68 °F: Non-applicable *

Solubility in water at 68 °F: Non-applicable *

Solubility properties: Immiscible

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: >302 °F

Flammability (solid, gas): Non-applicable *

Autoignition temperature: Non-applicable *

Lower flammability limit: Non-applicable *

Upper flammability limit: Non-applicable *

Explosive (Solid):

Lower explosive limit: Non-applicable *

Upper explosive limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

Corrosive to metals: Non-applicable *

Heat of combustion: Non-applicable *

Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 68 °F: Non-applicable *

Refraction index: Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Titanium dioxide (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: May damage fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Product-specific toxicological information:

Acute toxicity		Genus
LD50 oral	>5000 mg/kg	
LD50 dermal	>5000 mg/kg	
LC50 inhalation dust	>5 mg/L	

Specific toxicology information on the substances:

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
Bisphenol F diglycidyl ether resin CAS: 28064-14-4	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane CAS: 30499-70-8	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

12.2 Persistence and degradability:

Non-applicable

12.3 Bioaccumulative potential:

Non-applicable

12.4 Mobility in soil:

Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- | | |
|--|--|
| 14.1 UN number: | UN3077 |
| 14.2 UN proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Bisphenol F diglycidyl ether resin) |
| 14.3 Transport hazard class(es): | 9 |
| Labels: | 9 |
| 14.4 Packing group, if applicable: | III |
| 14.5 Marine pollutant: | Yes |
| 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises | |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 5 kg |
| Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft | |
| 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number: UN3077
- 14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Bisphenol F diglycidyl ether resin)
- 14.3 Transport hazard class(es): 9
Labels: 9
- 14.4 Packing group, if applicable: III
- 14.5 Marine pollutant: Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Special regulations: 335, 966, 274, 967, 969
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9
Limited quantities: 5 kg
Segregation group: Non-applicable
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



- 14.1 UN number: UN3077
- 14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Bisphenol F diglycidyl ether resin)
- 14.3 Transport hazard class(es): 9
Labels: 9
- 14.4 Packing group, if applicable: III
- 14.5 Marine pollutant: Yes
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations specific for the product in question:

**BELZONA® 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): *Bisphenol F diglycidyl ether resin (28064-14-4)* ; *1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane (30499-70-8)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Non-applicable
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK - Substance List: Non-applicable
- Minnesota - Hazardous substances ERTK: Non-applicable
- New Jersey Worker and Community Right-to-Know Act: Non-applicable
- New York RTK - Substance list: Non-applicable
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: Non-applicable
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Bisphenol F diglycidyl ether resin (28064-14-4)*
- Rhode Island - Hazardous substances RTK: Non-applicable
- SB-258 Cleaning Product Right to Know Act : Non-applicable
- The Toxic Substances Control Act (TSCA) : *Bisphenol F diglycidyl ether resin (28064-14-4)* ; *1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane (30499-70-8)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Section: 1, 2, 3, 5, 8, 11, 15, 16

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H360: May damage fertility or the unborn child.

H319: Causes serious eye irritation.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

**BELZONA[®] 1813 - BASE
SN2693**

Date of compilation: 3/20/2024

Revised: 4/11/2025

Version: 1.1 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon
IARC: International Agency for Research on Cancer

Date of compilation: 3/20/2024

Revised: 4/11/2025

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET