

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 1: IDENTIFICATION

1.1 Product identifier: BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833

Other means of identification:

Non-applicable

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses (Industrial user): Resins for making composites

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:

Belzona Limited
Claro Road
HG1 4DS Harrogate - North Yorkshire - England
Phone: +441423567641
sds@belzona.com
https://www.belzona.com

Belzona Inc.
14300 NW 60th Ave.
Miami Lakes
FL 33014
UNITED STATES
Telephone: 1-305-594-4994

1.4 Emergency phone number: VelocityEHS: +1 813-248-0585 (International) (24/7/365)

US, Puerto Rico & the U.S. Virgin Islands: 1-800-255-3924 (24/7)

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

NFPA:

Health Hazards: 3

Flammability Hazards: 1

Instability Hazards: 0

Special Hazards: Non-applicable

29 CFR 1910.1200:

Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

2.2 Label elements:

NFPA:



29 CFR 1910.1200:

Danger



Hazard statements:

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024 Revised: 4/1/2025 Version: 1.2 (Replaced 1.1)

SECTION 2: HAZARD(S) IDENTIFICATION (continued)

Acute Tox. 4: H332 - Harmful if inhaled.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Precautionary statements:

P260: Do not breathe vapors.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing and eye protection.
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor.
P333+P313: If skin irritation or rash occurs: Get medical attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P405: Store locked up.
P501: Dispose of the contents/container in accordance with all Federal, State/Provincial and local regulations.

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Formulated polyamines

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name	Concentration
CAS: 1477-55-0	m-phenylenebis(methylamine)	10 - <30 %
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	10 - <30 %
CAS: 71074-89-0	Bis[(dimethylamino)methyl]phenol	1 - <5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 4: FIRST-AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC), Water Mist Extinguisher (AC)

Unsuitable extinguishing media:

Water jet

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

- CONTINUED ON NEXT PAGE -

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024 Revised: 4/1/2025 Version: 1.2 (Replaced 1.1)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits	
	PEL	STEL
m-phenylenebis(methylamine) CAS: 1477-55-0		0.1 mg/m ³

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.2 Appropriate engineering controls:


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
	Continuous flow compressed air line breathing device (Filter type: ABEK)	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.
	Filter mask for gases and vapours (Filter type: ABEK)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands



Pictogram	PPE	Remarks
	Chemical protective gloves (Material: Nitrile, Breakthrough time: 10 - 30 min, Thickness: 0.12 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
	Work clothing	Replace before any evidence of deterioration.
	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024 Revised: 4/1/2025 Version: 1.2 (Replaced 1.1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Corrosive to the respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Product-specific toxicological information:

Acute toxicity		Genus
LD50 oral	2639.15 mg/kg	
LD50 dermal	>5000 mg/kg	

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
m-phenylenebis(methylamine) CAS: 1477-55-0	LD50 oral	930 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour	1.34 mg/L (4 h)	Rat
	LC50 inhalation mist	1.34 mg/L	Rat
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2	LD50 oral	2169 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50			
m-phenylenebis(methylamine) CAS: 1477-55-0	LC50	88 mg/L (96 h)	Oryzias latipes	Fish
	EC50	15 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC			
m-phenylenebis(methylamine) CAS: 1477-55-0	NOEC	Non-applicable		
	NOEC	4.7 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5		Concentration	
m-phenylenebis(methylamine) CAS: 1477-55-0	BOD5	Non-applicable	Concentration	14 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	49 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	
m-phenylenebis(methylamine) CAS: 1477-55-0	BCF	3
	Pow Log	0.18
	Potential	Low
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2	BCF	
	Pow Log	0.22
	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc		Henry	
m-phenylenebis(methylamine) CAS: 1477-55-0	Koc	1300	Henry	Non-applicable
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Other information:

Labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations.

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis (methylamine); Formaldehyde polymer with 1,3-benzenedimethanamine and phenol)

14.3 Transport hazard class(es): 8

Labels: 8

14.4 Packing group, if applicable: II

14.5 Marine pollutant: Yes

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

Limited quantities: 1 L

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number:** UN2735
- 14.2 UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis (methylamine); Formaldehyde polymer with 1,3-benzenedimethanamine and phenol)

14.3 Transport hazard class(es): 8

Labels: 8

14.4 Packing group, if applicable: II

14.5 Marine pollutant: Yes

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Special regulations: 274

EmS Codes: F-A, S-B

Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: SGG18

14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

Transport of dangerous goods by air:

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IATA/ICAO 2025:



14.1 UN number:	UN2735
14.2 UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis (methylamine); Formaldehyde polymer with 1,3-benzenedimethanamine and phenol)
14.3 Transport hazard class(es):	8
Labels:	8
14.4 Packing group, if applicable:	II
14.5 Marine pollutant:	Yes
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *m-phenylenebis(methylamine) (1477-55-0)*; *2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)*; *Bis(dimethylamino)methylphenol (71074-89-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): *m-phenylenebis(methylamine) (1477-55-0)*; *2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Non-applicable
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK - Substance List: *m-phenylenebis(methylamine) (1477-55-0)*
- Minnesota - Hazardous substances ERTK: *m-phenylenebis(methylamine) (1477-55-0)*
- New Jersey Worker and Community Right-to-Know Act: *m-phenylenebis(methylamine) (1477-55-0)*
- New York RTK - Substance list: *m-phenylenebis(methylamine) (1477-55-0)*
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: *m-phenylenebis(methylamine) (1477-55-0)*
- Protective Action Criteria (PAC) with AEGs, ERPGs, & TEELs: *2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)*
- Rhode Island - Hazardous substances RTK: Non-applicable
- SB-258 Cleaning Product Right to Know Act : Non-applicable
- The Toxic Substances Control Act (TSCA) : *m-phenylenebis(methylamine) (1477-55-0)*; *2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

**BELZONA® 1982 - SUPERWRAP II - TROPICAL GRADE - SOLIDIFIER
SN2833**

Date of compilation: 11/21/2024

Revised: 4/1/2025

Version: 1.2 (Replaced 1.1)

SECTION 16: OTHER INFORMATION (continued)

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Section: 1, 2, 3, 5, 8, 11, 15, 16

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

Advice related to training:

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 11/21/2024

Revised: 4/1/2025

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET